



OpenFlows[™] Sewer Comparison Chart

	OpenFlows Sewer Ultimate	OpenFlows Sewer Advanced	OpenFlows Sewer Standard	OpenFlows Sewer Essentials
Sizing	Unlimited Pipes	≤5,000 pipes	≤1,000 pipes	≤100 pipes
Run OpenFlows Sewer within MicroStation®, OpenRoads™ Designer, OpenSite® Designer*, OpenRail™ Designer*, AutoCAD*, or as a stand-alone interface	•	•	•	•
Run OpenFlows Sewer within ArcGIS* and ArcGIS Pro*	•	*		
Model Building				
Automated catchment delineation from terrain	+	*	*	*
Automatic sanitary load allocation from geospatial data, flow monitors, and property connections	•	•	•	•
Creation of model elements from CAD drawings	*	*	*	*
Import/export of LandXML, MX Drainage, and InRoads® storm and sanitary data.	•	•	•	•
Seed files for new model templates	•	*	*	*
Model building and synchronization with shapefiles, spreadsheets, databases, Oracle Spatial, and open database connectivity connections	•	•	•	•
Model building and synchronization with geodatabases, geometric networks, and SDE	•	•		
Automated NRCS curve number and rational "c" weighting from land use polygons	•	•		
SCADAConnect® for live system data connections	•	*		
Import/export of SWMM and MicroDrainage model files	•	*		
Scenario and Model Management				
Comprehensive, unlimited scenario management	*	*	*	*
Active topology to activate or deactivate network elements	•	•	*	•
Customizable engineering libraries	*	*	*	*
Dynamic and static selection sets	•	•	*	•
Orphan node and dead-end pipe queries	*	*	*	*
Surface flow path tracing from terrain	*	*	*	*
ProjectWise® integration	•	*	*	*

^{*}License Required

Hydraulics and Operations	OpenFlows Sewer Ultimate	OpenFlows Sewer Advanced	OpenFlows Sewer Standard	OpenFlows Sewer Essentials
GVF-convex solver for steady-state and extended-period simulations for sewer (convex routing and EPANET-based pressure network solution)	•	•	•	•
Extreme flow factors for use with steady-state simulation	*	*	*	*
Energy cost analysis	*	*	*	*
Air valves for high points in force mains	•	*	*	*
Low-impact development controls	*	*	*	*
Rule-based controls	*	*	*	*
Tractive stress calculation	*	*	*	*
Variable-speed pumps	•	*	*	*
Totalizing flow meters	•	*	*	*
Ability to model individual property connections, taps, and laterals	*	*	*	*
Inline control structures and diversions** (weirs, orifices, and depth-flow curves)	•	•	* **	◆ **
Automatic constraint-based design of gravity systems	•	*	*	•
HEC-22 node headloss calculations	*	*	*	*
HEC-22 inlet capacity calculations	•	*		
Two solvers for the full set of 1D Saint-Venant equations: implicit dynamic and explicit dynamic (EPA-SWMM)	*	•		
GVF-rational solver for stormwater (rational method flow calculation)	•	*		
Long-term continuous simulation	*	*		
1D/2D hydraulic analysis for surface flood modeling	*	*		
Critical storm analysis	*	*		
Hydrogen sulfide formation	*	*		
V-shaped and parabolic gutters	*	*		
Culvert headwalls with SWMM and HDS-5 culvert support	*	*		
Evaporation definition	•	*		
Hydrogen sulfide formation	•	*		
Aquifer simulation	*	*		
Pollutant analysis with optional definition of land use categories and surface characteristics	•	•		
Results Presentation	<i>,</i>			
Thematic mapping with color coding	*	*	*	*
Scenario and element comparison	*	•	*	•
ArcGIS Pro* visualization	*	*		
Grid browser for visualizing 2D surface input and output data	*	*		
Gutter cross section viewer	*	*		

^{*}License Required
**Diversion structures require manual rating table definition at this feature level



FIND OUT MORE AT BENTLEY.COM

1.800.BENTLEY (1.800.236.8539) | Outside the US +1.610.458.5000 | **GLOBAL OFFICE LISTINGS** bentley.com/contact